

ALPHA STAINLESS

8470UFD100P30 BLUE TFR

EAN 4031582391923



Image may differ from the original product

PERFORMANCE

Roll performance	● ● ● ○ ○
Movement noise	● ● ● ● ●
Attrition	● ● ● ○ ○
Corrosion resistance	● ● ● ● ●

CORE ATTRIBUTES

Product name	Alpha stainless
Housing type	Swivel castor
Standard	EN12532 - Transport Equipment
Load capacity at 4 km/h	150 kg
Load capacity Static	300 kg
Temperature range (Minimum)	-20 °C
Temperature range (Maximum)	80 °C
Overall height	128 mm
Overall weight	0.811 kg



WHEEL

BETTER MOBILITY. BETTER LIFE.

Body material	Polyamide
Web Wheel Dropdown	Elastic tire, non-marking, vulcanized, Roller bearing, stainless (U F D)
Tread material	Elastic tire, non-marking, vulcanized
Bearing	Roller bearing, stainless
Diameter	100 mm
Tread width	34 mm
Hardness of tread (A)	64 Shore A

HOUSING

Material	Stainless steel, heavy
Fork shape	Broad
Swivel bearing	Two ball races
Offset	41 mm
Swivel radius	91 mm
Swivel interference	182 mm
Stainless	✓

FITTING

Fitting type	Bolt hole
Web Fitting Dropdown	Bolt hole 13 Millimetre (P30)
Bolt hole diameter	13 mm

ALPHA STAINLESS

8470UFD100P30 BLUE TFR

EAN 4031582391923



BETTER MOBILITY. BETTER LIFE.

TECHNICAL DRAWINGS

