

ALPHA STAINLESS

8470UOD125P30-13

EAN 4031582373424



Image may differ from the original product

PERFORMANCE

Roll performance	● ● ● ● ○
Movement noise	● ● ○ ○ ○
Attrition	● ● ● ● ●
Corrosion resistance	● ● ● ● ●

CORE ATTRIBUTES

Product name	Alpha stainless
Housing type	Swivel castor
Standard	EN12532 - Transport Equipment
Load capacity at 4 km/h	150 kg
Load capacity Static	300 kg
Temperature range (Minimum)	-40 °C
Temperature range (Maximum)	80 °C
Overall height	155 mm
Overall weight	0.868 kg



WHEEL BETTER MOBILITY. BETTER LIFE.

Body material	Polyamide
Web Wheel Dropdown	Polyamide, Roller bearing, stainless (U O D)
Tread material	Identical with wheel body
Bearing	Roller bearing, stainless
Axle	Screwed with nut
Diameter	125 mm
Tread width	40 mm
Hardness of tread (D)	75 Shore D

HOUSING

Material	Stainless steel, heavy
Fork shape	Broad
Swivel bearing	Two ball races
Offset	40 mm
Swivel radius	102.5 mm
Swivel interference	205 mm
Stainless	✓

FITTING

Fitting type	Bolt hole
Web Fitting Dropdown	Bolt hole 13 Millimetre (P30)
Bolt hole diameter	13 mm

ALPHA STAINLESS

8470UOD125P30-13

EAN 4031582373424



BETTER MOBILITY. BETTER LIFE.

TECHNICAL DRAWINGS

