

B-POEV 125KA-SB

Pressed steel fixed castor, medium duty design, with top plate fitting, heavy duty wheel, with 'Blickle EasyRoll' elastic solid rubber tyres, with nylon wheel centre, non-marking, blue, with synthetic thread guard, small

EAN 4047526674342

ID 674341

Customs tariff number 87169090



Bracket: B series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

Wheel: POEVseries

- tyre: high-quality elastic solid rubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, colour blue, non-marking
- wheel centre: high-quality nylon 6, impact resistant, colour black

Other features:

- with synthetic thread guard, small
- high chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +80 °C, temporarily up to +100 °C, reduced load capacity over +35 °C



Technical data:

Wheel Ø(D)	☐	125 mm
Wheel width	☐	37 mm
Load capacity at 4 km/h	☐	250 kg
Load capacity (static)	☐	625 kg
Bearing type	☐	ball bearing (C)
Total height (H)	☐	150 mm
Installation type		top plate
Plate size	☐	100 x 85 mm
Bolt hole spacing	☐	80 x 60 mm
Bolt hole Ø	☐	9 mm
Temperature resistance min		-20 °C
Temperature resistance max		80 °C
Tread and tyre hardness		65 Shore A
Unit weight	☐	0.7 kg
Non-marking		✓
Non-staining		✓
Antistatic	☐	✗
ESD		✗
Electrically conductive	☐	✗
Corrosion-resistant		✗
Heat-resistant	☐	✗
Suitable for autoclaves		✗
Suitable for machine washing		✗

Tread and tyre hardness

■■■■■ 65 Shore A

Rolling resistance

■■■■■ very good

Wear resistance

■■■■■ good

Operating noise / floor surface preservation

■■■■■ very good

