

BK-POTH 125KA-1

Pressed steel fixed castor, heavy duty design, with top plate fitting, wheel, with thermoplastic polyurethane tread, with heavy duty nylon wheel centre, with synthetic thread guard, small

EAN 4047526280154

ID 280156

Customs tariff number 87169090



Bracket: BK series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free

Wheel: POTH series

- tread: high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A, colour dark grey, non-marking, non-staining
- wheel centre: high-quality nylon 6, impact resistant, colour natural white

Other features:

- with synthetic thread guard, small
- very high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +70 °C, temporarily up to +90 °C, reduced load capacity over +35 °C

Technical data:

Wheel Ø(D)	125 mm
Wheel width	40 mm
Load capacity at 4 km/h	350 kg
Load capacity (static)	875 kg
Bearing type	ball bearing (C)
Total height (H)	155 mm
Installation type	top plate
Platesize	100 x 85 mm
Bolt hole spacing	80 x 60 mm
Bolt hole Ø	9 mm
Temperature resistance min	-20 °C
Temperature resistance max	70 °C
Tread and tyre hardness	94 ShoreA
Unit weight	0.8 kg
Non-marking	✓
Non-staining	✓
Antistatic	×
ESD	×
Electrically conductive	×
Corrosion-resistant	×
Heat-resistant	×
Treadhydrolysis-resistant	×
Suitable for autoclaves	×
Suitable for machine washing	×



Tread and tyre hardness

■ ■ ■ ■ □ 94 ShoreA

Rolling resistance

■ ■ ■ ■ □ very good

Wear resistance

■ ■ ■ ■ □ very good

Operating noise / floor surface preservation

■ ■ ■ □ □ good

