

LE-POEV 100KA-SB

Pressed steel swivel castor, with top plate fitting, heavy duty wheel, with 'Blickle EasyRoll' elastic solid rubber tyres, with nylon wheel centre, non-marking, blue, with synthetic thread guard, small

EAN 4047526605063

ID 605063

Customs tariff number 87169090



Bracket: LE series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: POEV series

- tyre: high-quality elasticsolidrubber "Blickle EasyRoll" in smooth rolling quality, hardness 65 Shore A, colour blue, non-marking
- wheel centre: high-quality nylon 6, impact resistant, colour black



Other features:

- with synthetic thread guard, small
- high chemical resistance to many aggressive substances, except oils
- operating temperature: -20 °C to +80 °C, temporarily up to +100 °C, reduced load capacity over +35 °C

Technical data:

Wheel Ø(D)	100 mm
Wheel width	32 mm
Load capacity at 4 km/h	150 kg
Load capacity (static)	375 kg
Bearing type	ball bearing (C)
Total height (H)	125 mm
Mounting type	top plate
Platesize	100 x 85 mm
Bolt hole spacing	80 x 60 mm
Bolt hole Ø	9 mm
Offset (F)	36 mm
Temperature resistance min	-20 °C
Temperature resistance max	70 °C
Tread and tyre hardness	65 ShoreA
Unit weight	0.7 kg
Non-marking	✓
Non-staining	✓
Antistatic	✗
ESD	✗
Electrically conductive	✗
Corrosion-resistant	✗
Heat-resistant	✗
Suitable for autoclaves	✗

Tread and tyre hardness

■ ■ ■ ■ ■ 65 ShoreA

Rolling resistance

■ ■ ■ ■ ■ very good

Wear resistance

■ ■ ■ ■ ■ good

Operating noise / floor surface preservation

■ ■ ■ ■ ■ very good

