

LH-GTH 150K-FI

Pressed steel swivel castor, heavy duty design, with top plate fitting, with brake system 'stop-fix', heavy duty wheel, with Blickle Extrathane® polyurethane tread, with cast iron wheel centre

EAN 4047526513795
ID 513796
Customs tariff number 87169090



Bracket: LH series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- heavy fork and top plate
- double ball bearing in the swivel head
- bolted and secured central kingpin, extremely strong
- particularly resistant to shocks and impact due to four specially-shaped, hardened bearing seats

Wheel: GTH series

- tread: high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A, colour yellow, non-marking, non-staining
- wheel centre: rugged grey cast iron
- with grease nipple, lacquered, colour silver



Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +70 °C, temporarily up to +90 °C, reduced load capacity over +40 °C

Technical data:

Wheel Ø(D)	150 mm
Wheel width	50 mm
Load capacity at 4 km/h	800 kg
Load capacity (static)	2,000 kg
Bearing type	ball bearing
Total height (H)	197 mm
Installation type	top plate
Platesize	140 x 110 mm
Bolt hole spacing	105 x 75–80 mm
Bolt hole Ø	11 mm
Offset (F)	56 mm
Temperature resistance min	-20 °C
Temperature resistance max	70 °C
Tread and tyre hardness	92 Shore A
Unit weight	6kg
Non-marking	✓
Non-staining	✓
Antistatic	X
ESD	X
Electrically conductive	X
Corrosion-resistant	X
Heat-resistant	X

Tread and tyre hardness

■■■■■□ 92 Shore A

Rolling resistance

■■■■■□ very good

Wear resistance

■■■■■□ excellent

Operating noise / floor surface preservation

■■■■■□ good

