

LH-GTH 200K-FI

Pressed steel swivel castor, heavy duty design, with top plate fitting, with brake system 'stop-fix', heavy duty wheel, with Blickle Extrathane® polyurethane tread, with cast iron wheel centre

EAN 4047526474829

ID 474825

Customs tariff number 87169090



Bracket: LH series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- heavy fork and top plate
- double ball bearing in the swivel head
- bolted and secured central kingpin, extremely strong
- particularly resistant to shocks and impact due to four specially-shaped, hardened bearing seats

Wheel: GTH series

- tread: high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 ShoreA, colour yellow, non-marking, non-staining
- wheel centre: rugged grey cast iron
- with grease nipple, lacquered, colour silver



Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +70 °C, temporarily up to +90 °C, reduced load capacity over +40 °C

Technical data:

Wheel Ø(D)	200 mm
Wheel width	50 mm
Load capacity at 4 km/h	900 kg
Load capacity (static)	2,250 kg
Bearing type	ball bearing
Total height (H)	245 mm
Installation type	top plate
Platesize	140 x 110 mm
Bolt hole spacing	105 x 75–80 mm
Bolt hole Ø	11 mm
Offset (F)	61 mm
Temperature resistance min	-20 °C
Temperature resistance max	70 °C
Tread and tyre hardness	92 ShoreA
Unit weight	7.2 kg
Non-marking	✓
Non-staining	✓
Antistatic	×
ESD	×
Electrically conductive	×
Corrosion-resistant	×
Heat-resistant	×

Tread and tyre hardness

■■■■■□ 92 ShoreA

Rolling resistance

■■■■■□ very good

Wear resistance

■■■■■□ excellent

Operating noise / floor surface preservation

■■■■■□ good

