

LH-G150K-FI

Pressed steel swivel castor, heavy duty design, with top plate fitting, with brake system 'stop-fix', cast iron wheel

EAN 4047526629212

ID 629212

Customs tariff number 87169090



Bracket: LH series

- strong pressed steel, zinc-plated, blue-passivated, Cr6-free
- heavy fork and top plate
- double ball bearing in the swivel head
- bolted and secured central kingpin, extremely strong
- particularly resistant to shocks and impact due to four specially-shaped, hardened bearing seats

Wheel: G series

- rugged grey cast iron, hardness 180–220 HB, grease nipple, lacquered, colour silver

Other features:

- chemical resistance to many aggressive substances
- consider the surface pressure on sensitive floors due to high point loads
- to be lubricated according to the application temperature

Technical data:

Wheel Ø(D)	150 mm
Wheel width	50 mm
Load capacity at 4 km/h	900 kg
Load capacity (static)	2,250 kg
Bearing type	ball bearing
Total height (H)	197 mm
Installation type	top plate
Platesize	140 x 110 mm
Bolt hole spacing	105 x 75–80 mm
Bolt hole Ø	11 mm
Offset (F)	56 mm
Temperature resistance min	-20 °C
Temperature resistance max	120 °C
Tread and tyre hardness	180–220 HB
Unit weight	6.4 kg
Non-marking	X
Non-staining	✓
Antistatic	X
ESD	✓
Electrically conductive	✓
Corrosion-resistant	X
Heat-resistant	X
Suitable for autoclaves	X
Suitable for machine washing	X



Tread and tyre hardness

■■■■■ 180–220 HB

Rolling resistance

■■■■■ excellent

Wear resistance

■■■■■ excellent

Operating noise / floor surface preservation

■□□□□ sufficient

