

LPA-POA 35G

Light duty swivel castor, with top plate fitting, nylon wheel

EAN 4047526223878

ID 223875

Customs tariff number 83022000



Bracket: LPA series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- strong central kingpin
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: POA series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour black

Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -25 °C to +80 °C, reduced load capacity over +35 °C

Technical data:

Wheel Ø(D)	35 mm
Wheel width	25 mm
Load capacity at 3 km/h	75 kg
Load capacity (static)	190 kg
Bearing type	plain bore
Total height (H)	52 mm
Installation type	top plate
Platesize	60 x 60 mm
Bolt hole spacing	38 x 38 / 48 x 48 mm
Bolt hole Ø	6.2 mm
Offset (F)	15 mm
Temperature resistance min	-25 °C
Temperature resistance max	80 °C
Tread and tyre hardness	70 Shore D
Unit weight	0.2 kg
Non-marking	✓
Non-staining	✓
Antistatic	×
ESD	×
Electrically conductive	×
Corrosion-resistant	×
Heat-resistant	×
Suitable for autoclaves	×
Suitable for machine washing	×



Tread and tyre hardness

■■■■■ 70 Shore D

Rolling resistance

■■■■■ excellent

Wear resistance

■■■■■ good

Operating noise / floor surface preservation

■■■■■ satisfactory

