

LRA-POA 35G

Light duty swivel castor, with bolt hole fitting, nylon wheel

EAN 4047526226190

ID 226191

Customs tariff number 83022000



Bracket: LRA series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: POA series

- high-quality nylon 6, impact resistant, hardness 70 Shore D, colour black

Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -25 °C to +80 °C, reduced load capacity over +35 °C



Technical data:

Wheel Ø(D)	35 mm
Wheel width	25 mm
Load capacity at 3 km/h	75 kg
Load capacity (static)	190 kg
Bearing type	plain bore
Total height (H)	50 mm
Installation type	bolt hole
Plate Ø	43 mm
Bolt hole	11 mm
Offset (F)	15 mm
Temperature resistance min	-25 °C
Temperature resistance max	80 °C
Tread and tyre hardness	70 Shore D
Unit weight	0.1 kg
Non-marking	✓
Non-staining	✓
Antistatic	X
ESD	X
Electrically conductive	X
Corrosion-resistant	X
Heat-resistant	X
Suitable for autoclaves	X
Suitable for machine washing	X

Tread and tyre hardness

■■■■■ 70 Shore D

Rolling resistance

■■■■■ excellent

Wear resistance

■■■■■ good

Operating noise / floor surface preservation

■■■■■ satisfactory

