

LRA-VSTH 35K

Light duty swivel castor, with bolt hole fitting, heavy duty wheel, with Blickle Extrathane® polyurethane tread, with steel wheel centre

EAN 4047526226435
 ID 226431
 Customs tariff number 83022000



Bracket: LRAseries

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- double ball bearing in the swivel head
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: VSTH series

- tread: high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 ShoreA, colour yellow, non-marking, non-staining
- wheel centre: steel

Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +70 °C, temporarily up to +90 °C, reduced load capacity over +40 °C



Technical data:

Wheel Ø(D)	35 mm
Wheel width	27 mm
Load capacity at 3 km/h	100 kg
Load capacity (static)	250 kg
Bearing type	ball bearing
Total height (H)	50 mm
Installation type	bolt hole
Plate Ø	43 mm
Bolt hole	11 mm
Offset (F)	15 mm
Temperature resistance min	-20 °C
Temperature resistance max	70 °C
Tread and tyre hardness	92 ShoreA
Unit weight	0.2 kg
Non-marking	✓
Non-staining	✓
Antistatic	×
ESD	×
Electrically conductive	×
Corrosion-resistant	×
Heat-resistant	×
Treadhydrolysis-resistant	×
Suitable for autoclaves	×
Suitable for machine washing	×

Tread and tyre hardness

■ ■ ■ ■ ■ □ 92 ShoreA

Rolling resistance

■ ■ ■ ■ ■ □ very good

Wear resistance

■ ■ ■ ■ ■ excellent

Operating noise / floor surface preservation

■ ■ ■ □ □ good

